



linear dimension(Tolerances Standard GB/T 14486-2008)								—			
variable range	to	over 6	over 10	over 30	over 60	over 100	over 160	to	over 10	over 100	
		to 6	to 10	to 30	to 60	to 100	to 160		to 10	to 100	
tolerance		±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
A	新发行		CLF	22.05.06



UL/CUL 技术参数 UL/CUL Technical Data				
等级 Use Group		B	C	D
额定电压 Rated Voltage [V]		-	-	-
额定电流 Rated Current [A]		-	-	-
接线范围 Wire Range		-		
单/多芯线 Solid/Stranded [AWG]		-		
IEC 技术参数 IEC Technical Data				
额定电压 Rated Voltage [V]		-		
额定电流 Rated Current [A]		-		
耐压 Withstanding Voltage [V/1Min]		-		
导线截面积 Conductor cross section		-		
硬质/柔性导线 Solid/flexible [mm ²]		-		
材料 Material				
绝缘材料 Insulation Material		PA66		
阻燃等级 Imflammability		UL94V-0		
导体材料 Contactor Material		-		
导体表面镀层 Contactive Coating		-		
一般参数 Other Data				
间距 Pitch [mm]		-		
极数 Poles [P]		-		
剥线长度 Stripping Length [mm]		-		
螺丝 Screw/扭矩 Torque(Max) [N.m]		-		
工作温度 Operating temperatur [°C]		-		
引针尺寸 Pin Dimensions [mm]		-		
PCB板孔径 PCB Hole Diameter [mm]		-		

DES.	SJD	DATE	22.05.06	单位/UNITS	mm	尺寸/SIZE	A4	比例/SCALE	1:1	第三视角/THIRD ANGLE PROJECTION	版本/REV	A
CHK.	BY	DATE	22.05.06	慈溪市科发电子有限公司 CIXI KEFA ELECTRONIC CO., LTD				名称/TITLE	 KFME4500A			
APP.	CLF	DATE	22.05.06									