



300V 8A
 Piles: 2-24P
 Pitch: 3.5mm(.138")/3.81mm (.150")

Material

Housing: PA66 (UL 94V-0)
 Pin header: Phosphor Bronze, Tin Plated

序号/Revno.	更改记录/Revision note	签名/signature	日期/date	设计/Designed by		绘图/drawing by		审核/checked by		批准/Approved by		备注/Remark		单位/units: mm											
														<table border="1"> <tr> <th colspan="2">未注公差 General Tolerance</th> </tr> <tr> <td>X.° ±2°</td> <td>X.° ±1°</td> </tr> <tr> <td>.X ±0.1</td> <td>.X ±1</td> </tr> <tr> <td>.XX ±0.05</td> <td>.XX ±0.5°</td> </tr> <tr> <td>.XXX ±0.01</td> <td></td> </tr> </table>		未注公差 General Tolerance		X.° ±2°	X.° ±1°	.X ±0.1	.X ±1	.XX ±0.05	.XX ±0.5°	.XXX ±0.01	
未注公差 General Tolerance																									
X.° ±2°	X.° ±1°																								
.X ±0.1	.X ±1																								
.XX ±0.05	.XX ±0.5°																								
.XXX ±0.01																									
				XINLAIYA ELECTRONIC CO., LTD		图名/File name		XY2500B-3.5		文件编号/File No.		页序/Sheet													
				XINLAIYA ELECTRONIC CO., LTD		新莱亚电子		-3.81																	