



300V 55A 12-6AWG 10.0mm<sup>2</sup>  
 Poles: 2P  
 Pitch: 10.5 mm (.413")

Housing: PA66(UL 94V-0)  
 Contact: Copper, Tin Plated  
 WireCage: Brass, Nickel Plated  
 Screw: M5, Steel, Cr3+ Zinc Plated  
 Torque: 2.0 N.m

设计/Designed by		绘图/Drawing by		审核/Checked by		批准/Approved by																	
图名/File name		文件编号/File No.		备注/Remark		未注公差 General Tolerance																	
XY268		XY268				<table border="1"> <tr> <td>X</td> <td>±0.2</td> <td>X'</td> <td>±0°</td> </tr> <tr> <td>.X</td> <td>±0.1</td> <td>.X'</td> <td>±0°</td> </tr> <tr> <td>.XX</td> <td>±0.05</td> <td>.XX'</td> <td>±0.5°</td> </tr> <tr> <td>.XXX</td> <td>±0.01</td> <td></td> <td></td> </tr> </table>		X	±0.2	X'	±0°	.X	±0.1	.X'	±0°	.XX	±0.05	.XX'	±0.5°	.XXX	±0.01		
X	±0.2	X'	±0°																				
.X	±0.1	.X'	±0°																				
.XX	±0.05	.XX'	±0.5°																				
.XXX	±0.01																						
页序/Sheet		单位/Units: mm																					

