


Poles: (2, 3, 4P)  
 Pitch: 8.25mm (.325")  
 Voltage Rating: 300V  
 Current Rating: 20A  
 Wire range: 22-12AWG 2.5mm<sup>2</sup>  
 Housing: PA66 (UL 94V-0)  
 Solder Pin: Brass, Tin Plated  
 Screw: Steel, M3.5 Nickel Plated  
 Torque: 0.5N.m

设计/Designed by		绘图/Drawing by		审核/Checked by		批准/Approved by		备注/Remarks	
图名/File name		文件编号/File No.		图名/File name		文件编号/File No.		图名/File name	
XY836VS-8.25				XY836VS-8.25				XY836VS-8.25	
产品图		页序/Sheet		产品图		页序/Sheet		产品图	
单位/Units: mm				单位/Units: mm				单位/Units: mm	
General Tolerance				General Tolerance				General Tolerance	
X. ±0.2		X.° ±2°		X. ±0.2		X.° ±2°		X. ±0.2	
.X ±0.1		.X° ±1°		.X ±0.1		.X° ±1°		.X ±0.1	
.XX ±0.05		.XX° ±0.5°		.XX ±0.05		.XX° ±0.5°		.XX ±0.05	
.XXX ±0.01				.XXX ±0.01				.XXX ±0.01	


**新莱亚电子**  
 XINLAIYA ELECTRONIC CO., LTD