



| 序号/Rev No | 名称/Title | 材料/Material | 文件编号/File No |
|-----------|------------------|----------------|----------------|
| 1 | XY2500KNHS-3.5塑壳 | PA66 (UL94V-0) | QJ/XYT-A202000 |
| 2 | XY2500KNH-3.5下盖 | PA66 (UL94V-0) | QJ/XYT-A202200 |
| 3 | XY2500KN按钮 | PA66 (UL94V-0) | QJ/XYT-A200600 |
| 4 | XY2500KN端子 | 铜+不锈钢 (镀锡) | QJ/XYT-A300300 |
| 5 | M2螺丝 | M2螺丝 (镀锌) | QJ/XYT-2148103 |

Note

Poles: P=2x(2P~20P)

Pitch: 3.5mm

Use and Performance

Wire range:28-16AWG, 1.5mm²

Strip length:9-10mm

Rated voltage:300V

Rated current:8A

Withstanding voltage:AC2500V/Min

Ambient temperature:-40℃~+105℃

Undeclared tolerance:DIN16901-140B

未注公差/Undeclared tolerance:DIN 16901-140B

| 尺寸(mm) Dimension(mm) | 0 1 | 1 3 | 3 6 | 6 10 | 10 15 | 15 22 | 22 30 | 30 40 | 40 53 | 53 70 | 70 90 | 90 120 | 120 160 | 160 200 | 200 250 |
|-------------------------|--------|--------|--------|---------|----------|----------|----------|----------|----------|----------|----------|-----------|------------|------------|------------|
| | ±0.10 | ±0.11 | ±0.12 | ±0.14 | ±0.17 | ±0.20 | ±0.24 | ±0.28 | ±0.33 | ±0.40 | ±0.50 | ±0.60 | ±0.75 | ±0.95 | ±1.15 |

| 设计/Designed by | 绘图/Drawing by | 审核/Checked by | 批准/Approved by |
|----------------|---------------|---------------|----------------|
| | | | |
| | | | 图名/Title |
| | | | 文件编号/File No. |
| | | | QJ/XYT-A101300 |
| | | | 版本/VER |
| | | | 00 |
| | | | 备注/Remark |
| | | | 单位/Units: mm |

| 序号/RevNo. | 更改记录/Revision note | 签名/Signature | 日期/Date |
|-----------|--------------------|--------------|---------|
| | | | |